

USEFUL INFORMATION FOR SNAPDRAGON 670 OWNERS.

DIMENSIONS.

LOA.	22'0"	6.70 M	DRAFT	F/K.3'9"	1.14M	BALLAST.	1450 lbs
LWL.	19'0"	5.79 M		T/K.2'8"	0.81M.	TONNAGE	4.75
		2.74 M	DISPLACEMENT.	3240 lbs		HEADROOM.	5'9"
BEAM.	8'0"	2.74 M.					

<u>SAILS.</u>	<u>LUFF</u>	<u>LEACH</u>	<u>FOOT</u>	<u>MATERIAL</u>	<u>AREA</u>
Mainsail	25'0"	27'0"	9'0"	7 oz	127 sq ft.
Workingjib	20'0"	17'0"	9'4"	7 oz	78 sq ft.
No.1.Genoa	27'0"	26'0"	12'7"	7 oz	160 sq.ft.
No.2.Genoa	24'0"	21'4"	10'6"	7 oz	112 sq ft
Storm jib	15'0"	11'0"	6'8"	7 oz	37 sq ft.
Spinnaker				1.6 oz	340 sq ft.

RIGGING.

I = 29'6"
J = 8'6"

Standing.

All measurements are less bottle screws, Bottle screws closed pin to pin 6 1/2"

Forestay	28' 9 1/2"
Backstay	23' 11"
Bridles, each	7' 1"
Main shrouds	28' 7 1/2"
Inner forestay	13' 9 1/2"
Lower aft shrouds	13' 9"
Construction	1/2" cic. 1 x 19 S/S.

Running.

Main halyard	58' 1/8"	circ 3 pre-stretched terylene.
Jib halyard	58' 1"	circ 3 pre-stretched terylene
Mainsheet	47' 1 1/2"	circ matted ulstron
Jib sheets	53' 1 1/2"	circ matted ulstron
Storm jib sheets	47' 1 1/4"	circ matted ulstron
Spinnaker halyard	58' 1"	circ 3 pre-stretched terylene
Spinnaker sheets each	33' 1 1/2"	circ matted ulstron
Spinnaker up/down haul	33' 3/4"	circ 3 pre-stretched terylene
Topping lift	58' 5/8"	circ 3 pre-stretched terylene
Construction:		3 strand pre-stretched or matted ulstron terylene.